



Accessories Rolamentos do Brasil Ltda.



FYRP 3.7/16 Bearing 2D drawings and 3D CAD models

SKF FYRP 3.7/16 Flange Block Bearings

Bearing No. FYRP 3.7/16

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	13.39
EAN	7316576664984
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22218
Seals	Trigard
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 3-7/16" Bore; 8.6" Bolt Circle; 6.1" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 4-1/32" Length Thru B



Accessories Rolamentos do Brasil Ltda.

Other Features	Double Row Heavy Duty Open End With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FYRP 3.7/16
Weight / LBS	29.5
Cartridge Pilot Depth	1.25 Inch 31.75 Millimeter
d	3.438 Inch 87.325 Millimeter
Cartridge Pilot Diameter	7.375 Inch 187.32 Millimeter
D	4.031 Inch 102.4 Millimeter
Nominal Bolt Circle Diameter Round	8.6 Inch 218.4 Millimeter
Bolt Spacing	6.1 Inch 154.9 Millimeter
bore diameter:	3-7/16 in
locking device:	Set Screw
bolt center-to-center length:	8.6250 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt circle diameter:	8-5/8 in
seal type:	Contact/Lip
overall length/diameter:	10.2500 in
overall depth:	4-7/32 in
flange mounting type:	Four-Bolt Piloted
radial dynamic load capacity:	56900 lb
bearing type:	Spherical Roller
radial static load capacity:	76400 lb



Accessories Rolamentos do Brasil Ltda.

housing construction:	Solid Flange Mount
operating temperature range:	Maximum of +110 ° F ° F
bore type:	Round
finish/coating:	Uncoated
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	222